

P02 SERIES

MODEL	WATT	+5V	+12V	VAC	SSR	ROHS
P02BG	40	8A	2.5A	95~260		●
P02BSR	40	8A	2.5A	95~260	●	
P02BSR3	40	8A	2.5A	95~260	●	

- MECHANISM DIMENSION (L*W*H) :152*107*40 (mm)
- CARTON DIMENSION (L*W*H) :340*310*270 (mm)
- WEIGHT: 440g / PIECE
- 11.67KGS(GW) / 24PCS / CARTON
- TWO OUTPUTS WITH MAXIMUM POWER FROM 40 TO 50 WATT
- LOW COST,HIGH RELIABILITY.
- HIGH EFFICIENCY.
- OVER VOLTAGE PROTECTION.
- OVER CURRENT PROTECTION.
- LOW RIPPLE NOISE AT FULL LOADING.
- LOW WORKING TEMPERATURE.
- WITH SSR TO SUPPORT AND HOPPER CONTROL.

Input Voltage	95~260VAC
Input Frequency	47~63Hz
Input Current	0.6A~1.8A
Inrush Current	20A
Efficiency	75%
Load Variation	3%
Noise And Ripple	50mV MAX
Operation Temperature	0~50°C
Electronically Isolated	Input~Output AC 3000V 1 Minute