

MODEL	SPECIFICATION			SAFETY	RoHs (Option)
	AC INPUT	DC OUTPUT	SSR		
P031	110/220V~	+5V 15A / +12V 2.5A / -5V 1A		CE	
P032	110/220V~	+5V 15A / +12V 2.5A / -5V 1A (METER)		CE	
P033	110/220V~	+5V 9A / +12V 2A / +24V 1.5A		CE	
P03C(WY03C)	110/220V~	+5V 15A / +12V 2.5A / -5V 1A			
P03CM(WY03CM)	110/220V~	+5V 15A / +12V 2.5A / -5V 1A (METER)			

P03 SERIES OUTPUT VOLTAGE AND CURRENT								
MODEL	WATT	+5V	+12V	+24V	-5V	CE	VAC	REMARK
P03C	110	15	2.5		1		110 / 220	
P03CM	110	15	2.5		1		110 / 220	METER
P031	110	15	2.5		1	●	110 / 220	
P032	110	15	2.5		1	●	110 / 220	METER
P033	110	9	2	1.5		●	110 / 220	

- MECHANISM DIMENSION (L*W*H) :184*130*54 (mm)
- CARTON DIMENSION (L*W*H) : 410*400*295 (mm)
- WEIGHT: 680g / PIECE
- 17.32KGS(GW) / 24PCS / CARTON
- THREE-FOUR OUTPUTS WITH MAXIMUM POWER FROM 110 TO 200 WATT DEPENDING ON THE MODEL
- LOW COST, HIGH RELIABILITY.
- HIGH EFFICIENCY.
- OVER VOLTAGE PROTECTION.
- OVER CURRENT PROTECTION.
- LOW RIPPLE NOISE AT FULL LOADING.
- LOW WORKING TEMPERATURE.
- GREEN LED INDICATOR WHEN VOLTAGE WITHIN +5V~5.3V
- RED LED INDICATOR WHEN VOLTAGE WITHOUT +5V~5.3V

Input Voltage	110~120 / 220~240 VAC
Input Frequency	47~63Hz
Input Current	2.4~5A / 1.2~2.8A
Inrush Current	40A
Efficiency	75%
Load Variation	2% MAX (+5V) 5% MAX (Other)
Noise And Ripple	25~50mV MAX (+5v) 150Mv max (Other)

Operation Temperature	0~50°C
Electronically Isolated	Input~Output AC 3000V 1 Minute