

MODEL	SPECIFICATION			SAFETY	RoHs (Option)
	AC INPUT	DC OUTPUT	SSR		
P06A12	110/220V~	+12V 8.5A			

P06 SERIES OUTPUT VOLTAGE AND CURRENT								
MODEL	WATT	+3.3V	+5V	+12V	+15V	+24	-5V	VAC
P06A12	100			8.5				110 / 220

- MECHANISM DIMENSION (L*W*H) :188*98*38 (mm)
- CARTON DIMENSION (L*W*H) :450*380*220 (mm)
- WEIGHT: 620g / PIECE
- 16.0KGS(GW) / 24PCS / CARTON
- ONE-THREE OUTPUTS WITH MAXIMUM POWER FROM 100 TO 110 WATT DEPENDING ON THE MODEL
- LOW COST, HIGH RELIABILITY.
- HIGH EFFICIENCY.
- OVER VOLTAGE PROTECTION.
- OVER CURRENT PROTECTION.
- LOW RIPPLE NOISE AT FULL LOADING.
- LOW WORKING TEMPERATURE.

Input Voltage	100~120 / 220~240 VAC
Input Frequency	47~63Hz
Input Current	2.8 / 1.4 A
Inrush Current	40A
Efficiency	75%
Load Variation	2% MAX (+5V)
Noise And Ripple	50mV
Operation Temperature	0~50°C
Electronically Isolated	Input~Output AC 3000V 1 Minute