

MODEL	SPECIFICATION			SAFETY	RoHs (Option)
	AC INPUT	DC OUTPUT	SSR		
P15C1G(WY-15C1G)	110/220V~	+5V 15A / +12V 4A / -5V 1A		CE	●
P15CA1G(WY15CA1G)	110/220V~	+5V 9A /+12V 4A / +24V 1.5A		CE	●
P15CF(WY15CF)	110/220V~	+5V 20A / +12V 5A / -5V 2A (FAN)		CE	
P15CF1(WY15CF1)	110/220V~	+5V 15A / +12V 4A / -12V 1A			
P15CG2G(WY15CG2G)	110/220V~	+5V 15A / +12V 8A /+24V 5A		CE	●
P15DG(WY15DG)	110/220V~	+5V 4A / +12V 2A / +24V 2A/ +48V 1.8A		CE	●

P15 SERIES OUTPUT VOLTAGE AND CURRENT											
MODEL	WATT	+5V	+12V	+24V	+36V	+48V	-5V	-12V	CE	VAC	REMARK
P15C1G (WY15C1G)	130	15	4				1		●	110 / 220	R/G LED
P15CA1G (WY15CA1)	130	9	4	1.5					●	110 / 220	R/G LED
P15CF (WY15CF)	170	20	5				2		●	110 / 220	WITH FAN
P15CF1 (WY15CF1)	135	15	4					1		110 / 220	
P15CG2G (WY15CG2)	160	15	8	5					●	110 / 220	R/G LED
P15DG (WY15DG)	180	4	2	2		1.8			●	110 / 220	

- MECHANISM DIMENSION (L*W*H) :188*130*54 (mm)
- CARTON DIMENSION (L*W*H) :410*410*305 (mm)
- WEIGHT: 740g (P15DG), 670g (Other) / PIECE
- 18.8KGS(P15DG), 17.0KGS (Other) (GW) / 24PCS / CARTON
- THREE-FOUR OUTPUTS WITH MAXIMUM POWER FROM 110 TO 200 WATT DEPENDING ON THE MODEL
- LOW COST, HIGH RELIABILITY.
- HIGH EFFICIENCY.
- OVER VOLTAGE PROTECTION.
- OVER CURRENT PROTECTION.
- LOW RIPPLE NOISE AT FULL LOADING.
- LOW WORKING TEMPERATURE.
- GREEN LED INDICATOR WHEN VOLTAGE WITHIN +5V~5.3V.
- RED LED INDICATOR WHEN VOLTAGE WITHOUT +5V~5.3V.

Input Voltage	100~120 / 220~240 VAC
Input Frequency	47~63Hz
Input Current	2.4~5A / 1.2~2.8A
Inrush Current	40A
Efficiency	75%
Load Variation	2% MAX(+5V) 5% MAX (Other)
Noise And Ripple	25~50mV MAX(+5V) 150mV MAX(Other)
Operation Temperature	0~50°C
Electronically Isolated	Input~Output AC 3000V 1 Minute